




COMPACT BRAZED HEAT EXCHANGER

B10




The flexible B10 offers efficient heat exchange solutions across a wide capacity interval. The B10 is quick and simple to adapt for a number of applications. The product's flexibility and excellent heat transfer make it ideal for demanding cooling applications and sanitary water solutions, etc.

B10




STANDARD CONNECTIONS


For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.




Externally threaded




Internally threaded



Soldering



Int. Threaded with Hex. Ext.



Victaulic

TECHNICAL DATA

Max flow rate	12 m ³ /h (53 usg/min.)
Max working pressure at 155°C (311°F)	31 bar (450 psi)
Max working pressure at 225°C (437°F)	27 bar (392 psi)
Min working temperature	-196°C (-321°F)
Test pressure	50 bar (725 psi)
Max. Number of plates	120
CBE weight dry (approx.)	1.5+0.126×NP* kg (3.31+0.278×NP* lb)
Hold-up volume: inner circuit	0.061×(NP*/2-1) litre (0.016×(NP*/2-1) gal.)
Hold-up volume: outer circuit	0.061×NP*/2 litre (0.016×(NP*/2) gal.)
Standard connection size	1"
Connection height	20.1 mm (0.79 inch) or 45.1 mm (1.78 inch)

*NP = Number of plates

MATERIAL

Plate material:	EN 10028/7-1.4401 (AISI 316)
Brazing material:	Pure copper
Connection material:	EN 10272-1.4401 (AISI 316)

THIRD-PARTY APPROVALS (selection)

Europe, Pressure Equipment Directive (PED 97/23/EC)
 USA, Underwriters Laboratories (UL)
 Canada, Canadian Standard Association (CSA)
 Japan, The High Pressure Gas Safety Institute of Japan (KHK)

For additional information please contact your local SWEP representative.
 SWEP reserves the right to make changes without prior notice

THE B LINE - OUR BASIC RANGE

The majority of SWEP's CBEs are classified as B-types. The B-types are suitable for most applications. Although the B-type CBEs are "standard", there is a huge variety of plate sizes, port sizes, plate pattern combinations, connections etc. And SWEP's unique plate design enables a virtually unlimited number of combinations in any given plate package execution to precisely match the thermal transfer requirements of your application.



Easy to choose the right product solution

With SWEP's unique SSP CBE, the SWEP Software Package, you can do advanced heat transfer calculations yourself, and choose the product solution that suits your application best. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, or you would like to discuss different product solutions, SWEP offers all the service and support you need.

If you would like more information about B10 or our other products, please contact your local SWEP representative.

MC0209-04

January 2003

Copyright SWEP



SWEP INTERNATIONAL AB

Box 105, SE-261 22 Landskrona, Sweden
 Phone +46 418 540 00
 Fax +46 418 292 95
 Internet: www.swep.se
 E-mail: info@swep.se